



Model 650 Nitrogen Inflation System

8.6*
scfm

* 95% @ 160 psi / 75°
(standard factory setting)

Application: Automotive/ / Light Volume Truck

The Model 650 is perfect for those dealers who need a little more output but are concerned about space. This wall-mount unit has many of the same features as our tower systems... and with 8.6 SCFM of nitrogen output, it can easily handle the largest passenger and light truck shops as well as light volume commercial truck applications.



Specifications

Air Input	16.8 scfm @ 160 psi / 75° F
Air Input Range	100 psi to 175 psi
N2 Output	8.60 scfm @ 160 psi
N2 Purity	95% to 99.9%
N2 Dewpoint	-70° F
Operation Temp	40° to 150°F
Inlet Port	3/8 NPT
Outlet Port	3/8 NPT
N2 Purity Port	Yes
Auto Shut-Off	Yes
Pre-Filters	2
Maintenance Indicator (filters)	Yes
N2 Outlet Pressure Gauge	Yes
Dimensions	12" x 22" x 45"
Weight	155 Lbs
Wall Mounted	Yes

————Nitrogen Output————

95% Purity

4.6 scfm @ 100 psi
6.4 scfm @ 125 psi
8.0 scfm @ 150 psi
9.6 scfm @ 175 psi

98% Purity

2.6 scfm @ 100 psi
3.4 scfm @ 125 psi
4.4 scfm @ 150 psi
5.2 scfm @ 175 psi



Serving the Industry since 1923
4245 Main Avenue
Fargo, ND 58103
800-437-4394

www.branick.com

0106-233

To learn more about using **Nitrogen in Tires** go to www.GetNitrogen.org

GET NITROGEN[®] INSTITUTE

