



# Model 350 Nitrogen Inflation System

**1.78\***  
scfm

\* 95% @ 125 psi / 75°  
(standard factory setting)

## Application: Motorcycle / Light Volume Automotive

Intended for the smaller tire dealer, the Model 350 still uses the same membrane technology as our larger systems and requires minimum input pressure. This compact, wall-mount unit is also a real space saver. Designed for 1.78 scfm of nitrogen output, this entry level generator is the ideal solution for light-duty applications.



### Specifications

Air Input .....	3.55 scfm @ 125 psi / 75° F
Air Input Range .....	100 psi to 150 psi
N2 Output .....	1.78 scfm @ 125 psi
N2 Purity .....	95% to 99.9%
N2 Dewpoint .....	-70° F
Operation Temp .....	40° to 150°F
Inlet Port .....	1/4 NPT
Outlet Port .....	3/8 NPT
N2 Purity Port .....	No
Auto Shut-Off .....	No
Pre-Filters .....	3
Maintenance Indicator (filters) .....	No
N2 Outlet Pressure Gauge .....	Yes
Dimensions .....	12" x 22" x 48"
Weight .....	105 Lbs
Wall Mounted .....	Yes

#### — Nitrogen Output —

95% Purity	98% Purity
1.32 scfm @ 100 psi	.72 scfm @ 100 psi
1.78 scfm @ 125 psi	.97 scfm @ 125 psi
2.25 scfm @ 150 psi	1.23 scfm @ 150 psi

**Branick**   
Serving the industry since 1923  
4245 Main Avenue  
Fargo, ND 58103  
800-437-4304

[www.branick.com](http://www.branick.com)

0106-228

To learn more about using **Nitrogen in Tires** go to [www.GetNitrogen.org](http://www.GetNitrogen.org)

